



## ***MPC303X, MPC304X, MPC306X, MPC308X Series*** ***DIP6, DC Input, Zero-Cross Photo TRIAC Optocoupler***

### ■ Features

- High isolation 5000 VRMS
- DC input with zero-cross photo triac output
- Operating temperature range - 40 °C to 110 °C
- RoHS & REACH Compliance
- Halogen free
- MSL class 1
- Regulatory Approvals
  - UL - UL1577
  - VDE - EN60747-5-5(VDE0884-5)
  - CQC – GB4943.1, GB8898


### ■ Applications

- Solenoid/valve controls
- Lighting controls
- Motor controls
- Temperature controls
- Static AC power switches
- Solid state relays
- Interfacing microprocessors to 115 to 240VAC peripherals

### ■ Description

The MPC303X, MPC304X, MPC306X and MPC308X series combine an AlGaAs infrared emitting diode as the emitter which is optically coupled to a monolithic silicon zero-cross photo triac in a plastic DIP6 package with different lead forming options.

### ■ Schematic





***MPC303X, MPC304X, MPC306X, MPC308X Series***  
***DIP6, DC Input, Zero-Cross Photo TRIAC Optocoupler***

ABSOLUTE MAXIMUM RATINGS				
PARAMETER	SYMBOL	VALUE	UNIT	NOTE
INPUT				
Forward Current	$I_F$	60	mA	
Reverse Voltage	$V_R$	6	V	
Junction Temperature	$T_j$	125	°C	
Input Power Dissipation	$P_i$	100	mW	
OUTPUT				
Off-state Output Terminal Voltage	MPC303X	250	V	
	MPC304X	400		
	MPC306X	600		
	MPC308X	800		
Peak Repetitive Surge Current PW=100μs, 120pps	$I_{TSM}$	1	A	
Junction Temperature	$T_j$	125	°C	
Output Power Dissipation	$P_o$	300	mW	
COMMON				
Total Power Dissipation	$P_{tot}$	400	mW	
Isolation Voltage	$V_{iso}$	5000	V <sub>rms</sub>	1
Operating Temperature	$T_{opr}$	-40~100	°C	
Storage Temperature	$T_{stg}$	-55~125	°C	
Soldering Temperature	$T_{sol}$	260	°C	2

Note 1. AC For 1 Minute, R.H. = 40 ~ 60%

Note 2. For 10 seconds



**MPC303X, MPC304X, MPC306X, MPC308X Series**  
**DIP6, DC Input, Zero-Corss Photo TRIAC Optocoupler**

ELECTRICAL OPTICAL CHARACTERISTICS at Ta=25°C							
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION	NOTE
INPUT							
Forward Voltage	V <sub>F</sub>	-	1.24	1.4	V	I <sub>F</sub> =10mA	
Reverse Current	I <sub>R</sub>	-	-	10	μA	V <sub>R</sub> =6V	
Input Capacitance	C <sub>in</sub>	-	8.5	250	pF	V=0, f=1kHz	
OUTPUT							
Peak Off-state Current, Either Direction	I <sub>DRM</sub>	-	-	500	nA	V <sub>DRM</sub> =Rated V <sub>DRM</sub> I <sub>F</sub> =0	3
Peak On-state Current, Either Direction	V <sub>TM</sub>	-	1.59	2.5	V	I <sub>TM</sub> =100mA	
Critical Rate of Rise of Off-state Voltage	dV/dt	1000	-	-	V	V <sub>PEAK</sub> =Rated V <sub>DRM</sub>	4
TRANSFER CHARACTERISTICS							
LED Trigger Current	MPC3031, MPC3041, MPC3061, MPC3081	I <sub>FT</sub>	-	-	15	mA	Terminal Voltage = 3V I <sub>TM</sub> =100mA
	MPC3032, MPC3042, MPC3062, MPC3082		-	-	10		
	MPC3033, MPC3043, MPC3063, MPC3083		-	-	5		
Holding Current Saturation Voltage	I <sub>H</sub>	-	237	-	μA		
Isolation Resistance	R <sub>iso</sub>	10 <sup>12</sup>	10 <sup>14</sup>	-	Ω	DC500V, 40 ~ 60% R.H.	
Floating Capacitance	C <sub>IO</sub>	-	0.4	-	pF	V=0, f=1MHz	
ZERO-CROSS CHARACTERISTICS							
Inhibit Voltage	V <sub>INH</sub>	-	-	20	V	I <sub>F</sub> =Rated I <sub>FT</sub>	
Leakage in Inhibited State	I <sub>DRM2</sub>	-	-	500	μA	I <sub>F</sub> =Rated I <sub>FT</sub> V <sub>DRM</sub> =Rated V <sub>DRM</sub>	


Note3. Test voltage must be applied within dV/dt rating.

Note4. Refer to Fig.17 & Fig.18.




**MPC303X, MPC304X, MPC306X, MPC308X Series**  
**DIP6, DC Input, Zero-Corss Photo TRIAC Optocoupler**


**CHARACTERISTIC CURVES**




**Fig.1 Forward Current vs. Ambient Temperature**




**Fig.2 On-state Terminal Current vs. Ambient Temperature**




**Fig.3 Forward Current vs. Forward Voltage**



**Fig.4 Off-state Terminal Current vs. Ambient Temperature**



**Fig.5 Normalized Off-state Terminal Voltage vs. Ambient Temperature**




**Fig.6 Normalized Trigger Current vs. LED Trigger Pulse Width**




**MPC303X, MPC304X, MPC306X, MPC308X Series**  
**DIP6, DC Input, Zero-Corss Photo TRIAC Optocoupler**


**CHARACTERISTIC CURVES**




**Fig.7 Normalized Trigger Current vs. Ambient Temperature**




**Fig.8 On-state Terminal Voltage vs. Ambient Temperature**




**Fig.9 On-state Terminal Voltage vs. On-state Terminal Current**



**Fig.10 Holding Current vs. Ambient Temperature**




**Fig.11 Normalized Inhibit Voltage vs. Ambient Temperature**




**Fig.12 Normalized Leakage in Inhibit State vs. Ambient Temperature**

**CHARACTERISTIC CURVES**




**Fig.13 Turn On Time vs. Forward Current**




**Fig.14 Turn On Time vs. Ambient Temperature**


**TEST CIRCUITS**




**Fig.15 Test Circuits of Turn On Time**



**Fig.16 Waveforms of Turn On Time**



**Fig.17 Test Circuits of dV/dt**




**Fig.18 Waveforms of dV/dt**




***MPC303X, MPC304X, MPC306X, MPC308X Series***  
***DIP6, DC Input, Zero-Cross Photo TRIAC Optocoupler***

**PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)**

**Standard DIP-Through Hole(DIP Type)**




**Gullwing(400mil) Lead Forming-Through Hole(M Type)**




**PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)**

**Surface Mount Lead Forming(S Type)**



**Surface Mount(Low Profile) Lead Forming(SL Type)**









**MPC303X, MPC304X, MPC306X, MPC308X Series**  
**DIP6, DC Input, Zero-Cross Photo TRIAC Optocoupler**

**RECOMMENDED SOLDER MASK (Dimensions in mm unless otherwise stated)**

**Surface Mount Lead Forming & Surface Mount(Low Profile) Lead Forming**



**Surface Mount(Gullwing) Lead Forming**







**MPC303X, MPC304X, MPC306X, MPC308X Series**  
**DIP6, DC Input, Zero-Cross Photo TRIAC Optocoupler**

**CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)**

**Option S(T1) & SL(T1)**



**Option S(T2) & SL(T2)**






***MPC303X, MPC304X, MPC306X, MPC308X Series***  
***DIP6, DC Input, Zero-Corss Photo TRIAC Optocoupler***

**ORDERING AND MARKING INFORMATION**

**MARKING INFORMATION**



**MPC** : Company Abbr.  
**30XX** : Part Number&Rank  
**V** : VDE Option  
**Y** : Fiscal Year  
**A** : Manufacturing Code  
**WW** : Work Week

**ORDERING INFORMATION**

**MPC30XX(Y)(Z)-GV**

MPC – Company Abbr.

30XX – Part Number&Rank(31/32/33/41/42/43/61/62/63/81/82/83)

Y – Lead Form Option (M/S/SL/None)

Z – Tape and Reel Option (T1/T2)

G – Material Option (G: Green, None: Non-Green)


V – VDE Option (V or None)

**PACKING QUANTITY**

Option	Quantity	Quantity – Inner box	Quantity – Outer box
None	50 Units/Tube	32 Tubes/Inner box	10 Inner box/Outer box = 16k Units
M	50 Units/Tube	32 Tubes/Inner box	10 Inner box/Outer box = 16k Units
S(T1)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
S(T2)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
SL(T1)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units
SL(T2)	1000 Units/Reel	3 Reels/Inner box	5 Inner box/Outer box = 15k Units

**REFLOW INFORMATION**

**REFLOW PROFILE**



IPC-0204-5-1

Profile Feature	Sn-Pb Assembly Profile	Pb-Free Assembly Profile
Temperature Min. (T <sub>smin</sub> )	100	150°C
Temperature Max. (T <sub>smax</sub> )	150	200°C
Time (t <sub>s</sub> ) from (T <sub>smin</sub> to T <sub>smax</sub> )	60-120 seconds	60-120 seconds
Ramp-up Rate (t <sub>L</sub> to t <sub>p</sub> )	3°C/second max.	3°C/second max.
Liquidous Temperature (T <sub>L</sub> )	183°C	217°C
Time (t <sub>L</sub> ) Maintained Above (T <sub>L</sub> )	60 – 150 seconds	60 – 150 seconds
Peak Body Package Temperature	235°C +0°C / -5°C	260°C +0°C / -5°C
Time (t <sub>p</sub> ) within 5°C of 260°C	20 seconds	30 seconds
Ramp-down Rate (T <sub>p</sub> to T <sub>L</sub> )	6°C/second max	6°C/second max
Time 25°C to Peak Temperature	6 minutes max.	8 minutes max.



## ***MPC303X, MPC304X, MPC306X, MPC308X Series*** ***DIP6, DC Input, Zero-Cross Photo TRIAC Optocoupler***

### **DISCLAIMER**

- Our company is continually improving the quality, reliability, function and design. Our company reserves the right to make changes without further notices.
- The characteristic curves shown in this datasheet are representing typical performance which are not guaranteed.
- This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or lifesaving applications or any other application which can result in human injury or death.
- Immerge unit's body in solder paste is not recommended.
- Discoloration might be occurred on the package surface after soldering, reflow or long-time use. It neither impacts the performance nor reliability.

### ■ **Revision History**

<b>Version</b>	<b>Date</b>	<b>Subjects (major changes since last revision)</b>
1.0	2022-07-21	Datasheet Complete