



**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Cross Photo TRIAC Optocoupler

■ **Features**

- High isolation 5000 VRMS
- DC input with zero-cross photo triac output
- Operating temperature range - 40 °C to 100 °C
- RoHS & REACH Compliance
- Halogen free
- MSL class 1
- Regulatory Approvals
 - UL - UL1577
 - VDE - EN60747-5-5(VDE0884-5)
 - CQC – GB4943.1, GB8898

■ **Description**


The MPC303X-4L, MPC304X-4L and MPC306X-4L, MPC308X-4L series combine an AlGaAs infrared emitting diode as the emitter which is optically coupled to a monolithic silicon zero-cross photo triac in a plastic DIP4 package with different lead forming options.

With the robust coplanar double mold structure, MPC303X-4L, MPC304X-4L and MPC306X-4L, MPC308X-4L series provide the most stable isolation feature.

■ **Applications**

- Solenoid/valve controls
- Lighting controls
- Motor controls
- Temperature controls
- Static AC power switches
- Solid state relays
- Interfacing microprocessors to 115 to 240VAC peripherals

■ **Schematic**





**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Corss Photo TRIAC Optocoupler

ABSOLUTE MAXIMUM RATINGS					
PARAMETER		SYMBOL	VALUE	UNIT	NOTE
INPUT					
Forward Current		I_F	60	mA	
Reverse Voltage		V_R	6	V	
Junction Temperature		T_j	125	°C	
Input Power Dissipation		P_i	100	mW	
OUTPUT					
Off-state Output Terminal Voltage	MPC303X-4L	V_{DRM}	250	V	
	MPC304X-4L		400		
	MPC306X-4L		600		
	MPC308X-4L		800		
Peak Repetitive Surge Current PW=100μs, 120pps		I_{TSM}	1	A	
On-State RMS Current		$I_{T(RMS)}$	100	mA	
Junction Temperature		T_j	125	°C	
Output Power Dissipation		P_o	300	mW	
COMMON					
Total Power Dissipation		P_{tot}	400	mW	
Isolation Voltage		V_{iso}	5000	Vrms	1
Operating Temperature		T_{opr}	-40~100	°C	
Storage Temperature		T_{stg}	-55~150	°C	
Soldering Temperature		T_{sol}	260	°C	2

Note 1. AC For 1 Minute, R.H. = 40 ~ 60%

Note 2. For 10 seconds



**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Cross Photo TRIAC Optocoupler

ELECTRICAL OPTICAL CHARACTERISTICS at Ta=25°C							
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION	NOTE
INPUT							
Forward Voltage	V _F	-	1.24	1.4	V	I _F =10mA	
Reverse Current	I _R	-	-	10	μA	V _R =6V	
Input Capacitance	C _{in}	-	8.5	250	pF	V=0, f=1kHz	
OUTPUT							
Peak Off-state Current, Either Direction	I _{DRM}	-	-	100	nA	V _{DRM} =Rated V _{DRM} I _F =0	3
Peak On-state Current, Either Direction	V _{TM}	-	1.59	2.5	V	I _{TM} =100mA	
Critical Rate of Rise of Off-state Voltage Breakdown Voltage	dV/dt	1000	-	-	V	V _{PEAK} =Rated V _{DRM}	4
TRANSFER CHARACTERISTICS							
LED Trigger Current	MPC3031-4L, MPC3041-4L, MPC3061-4L, MPC3081-4L	I _{FT}	-	-	15	mA	Terminal Voltage = 3V I _{TM} =100mA
	MPC3032-4L, MPC3042-4L, MPC3062-4L, MPC3082-4L		-	-	10		
	MPC3032-4L, MPC3043-4L, MPC3063-4L, MPC3083-4L		-	-	5		
Holding Current Saturation Voltage	I _H	-	237	-	μA		
Isolation Resistance	R _{iso}	10 ¹²	10 ¹⁴	-	Ω	DC500V, 40 ~ 60% R.H.	
Floating Capacitance	C _{IO}	-	0.4	1	pF	V=0, f=1MHz	
ZERO-CROSS CHARACTERISTICS							
Inhibit Voltage	V _{INH}	-	-	20	V	I _F =Rated I _{FT}	
Leakage in Inhibited State	I _{DRM2}	-	-	500	μA	I _F =Rated I _{FT} V _{DRM} =Rated V _{DRM}	

Note3. Test voltage must be applied within dV/dt rating.

Note4. Refer to Fig.17 & Fig.18.



**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Cross Photo TRIAC Optocoupler

CHARACTERISTIC CURVES




Fig.1 Forward Current vs. Ambient Temperature




Fig.2 On-state Terminal Current vs. Ambient Temperature




Fig.3 Forward Current vs. Forward Voltage




Fig.4 Off-state Terminal Current vs. Ambient Temperature




Fig.5 Normalized Off-state Terminal Voltage vs. Ambient Temperature




Fig.6 Normalized Trigger Current vs. LED Trigger Pulse Width



**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Cross Photo TRIAC Optocoupler

CHARACTERISTIC CURVES




Fig.7 Normalized Trigger Current vs. Ambient Temperature




Fig.8 On-state Terminal Voltage vs. Ambient Temperature




Fig.9 On-state Terminal Voltage vs. On-state Terminal Current




Fig.10 Holding Current vs. Ambient Temperature




Fig.11 Normalized Inhibit Voltage vs. Ambient Temperature




Fig.12 Normalized Leakage in Inhibit State vs. Ambient Temperature

CHARACTERISTIC CURVES




Fig.13 Turn On Time vs. Forward Current




Fig.14 Turn On Time vs. Ambient Temperature

TEST CIRCUITS




Fig.15 Test Circuits of Turn On Time




Fig.16 Waveforms of Turn On Time




Fig.17 Test Circuits of dv/dt





Fig.18 Waveforms of dv/dt




**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Cross Photo TRIAC Optocoupler

PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Standard DIP – Through Hole (DIP Type)



Gullwing (400mil) Lead Forming – Through Hole (M Type)







**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Cross Photo TRIAC Optocoupler

PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Surface Mount Lead Forming (S Type)



Surface Mount (Low Profile) Lead Forming (SL Type)






**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Cross Photo TRIAC Optocoupler


PACKAGE DIMENSIONS (Dimensions in mm unless otherwise stated)

Surface Mount (Gullwing) Lead Forming (SLM Type)




RECOMMENDED SOLDER MASK (Dimensions in mm unless otherwise stated)

Surface Mount Lead Forming & Surface Mount (Low Profile) Lead Forming



Surface Mount (Gullwing) Lead Forming







**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Cross Photo TRIAC Optocoupler

CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option S(T1) & SL(T1)



Option S(T2) & SL(T2)







**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Cross Photo TRIAC Optocoupler

CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option S(T3) & SL(T3)



Option S(T4) & SL(T4)







**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Cross Photo TRIAC Optocoupler

CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)

Option SLM(T1)



Option SLM(T2)






**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Corss Photo TRIAC Optocoupler

ORDERING AND MARKING INFORMATION

MARKING INFORMATION



MPC : Company Abbr.
30XX : Part Number&Rank
V : VDE Option
Y : Fiscal Year
A : Manufacturing Code
WW : Work Week

ORDERING INFORMATION

MPC30XX-4L(Y)(Z)-GV

MPC – Company Abbr.
30XX –Part Number&Rank
(31/32/33/41/42/43/61/62/63
/81/82/83)

Y – Lead Form Option (M/S/SL/SLM/None)
Z – Tape and Reel Option (T1/T2/T3/T4)
G – Green
V – VDE Option (V or None)

PACKING QUANTITY


Option	Description	Quantity
None	Standard 4 Pin Dip	100 Units/Tube
M	Gullwing (400mil) Lead Forming	100 Units/Tube
S(T1)	Surface Mount Lead Forming – With Option 1 Taping	1500 Units/Reel
S(T2)	Surface Mount Lead Forming – With Option 2 Taping	1500 Units/Reel
S(T3)	Surface Mount Lead Forming – With Option 3 Taping	1000 Units/Reel
S(T4)	Surface Mount Lead Forming – With Option 4 Taping	1000Units/Reel
SL(T1)	Surface Mount (Low Profile) Lead Forming– With Option 1 Taping	1500 Units/Reel
SL(T2)	Surface Mount (Low Profile) Lead Forming – With Option 2 Taping	1500 Units/Reel
SL(T3)	Surface Mount (Low Profile) Lead Forming– With Option 3 Taping	1000 Units/Reel
SL(T4)	Surface Mount (Low Profile) Lead Forming – With Option 4 Taping	1000 Units/Reel
SLM(T1)	Surface Mount (Gullwing) Lead Forming– With Option 1 Taping	1500 Units/Reel
SLM(T2)	Surface Mount (Gullwing) Lead Forming – With Option 2 Taping	1500 Units/Reel



**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Corss Photo TRIAC Optocoupler

REFLOW INFORMATION

REFLOW PROFILE



IPC-020d-5-1

Profile Feature	Sn-Pb Assembly Profile	Pb-Free Assembly Profile
Temperature Min. (T _{smin})	100	150°C
Temperature Max. (T _{smax})	150	200°C
Time (t _s) from (T _{smin} to T _{smax})	60-120 seconds	60-120 seconds
Ramp-up Rate (t _L to t _P)	3°C/second max.	3°C/second max.
Liquidous Temperature (T _L)	183°C	217°C
Time (t _L) Maintained Above (T _L)	60 – 150 seconds	60 – 150 seconds
Peak Body Package Temperature	235°C +0°C / -5°C	260°C +0°C / -5°C
Time (t _P) within 5°C of 260°C	20 seconds	30 seconds
Ramp-down Rate (T _P to T _L)	6°C/second max	6°C/second max
Time 25°C to Peak Temperature	6 minutes max.	8 minutes max.



**MPC303X-4L, MPC304X-4L,
MPC306X-4L, MPC308X-4L Series**
DIP4, DC Input, Zero-Corss Photo TRIAC Optocoupler

DISCLAIMER

- Our company is continually improving the quality, reliability, function and design. Our company reserves the right to make changes without further notices.
- The characteristic curves shown in this datasheet are representing typical performance which are not guaranteed.
- This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or lifesaving applications or any other application which can result in human injury or death.
- Immerge unit's body in solder paste is not recommended.
- Discoloration might be occurred on the package surface after soldering, reflow or long-time use. It neither impacts the performance nor reliability.

■ Revision History

Version	Date	Subjects (major changes since last revision)
1.0	2018-12-21	Datasheet Complete